

# OILSPONGE

INDUSTRIAL STRENGTH CLEANER



## PRODUCT DATA SHEET

**Oil Sponge IS** is the toughest emulsion-based cleaner for your industrial needs.

**Oil Sponge IS** cleaner is strong enough for parts washers, but because of its low VOC (178 grams/liter concentrated and <25 grams/liter at typical dilution ratios) it is also appropriate for use with heated power washers or in other uncontained applications. Our emulsion-based alternative to mineral spirit solvents is non-flammable, non-toxic and bio-degradable.

**Oil Sponge IS** cleaner works wonders for the following; carbon build-up, petrol & synthetic oils, fats, greases and vegetable oils. **Oil Sponge IS** can also be utilized for smoke, soot, soils and general cleaning.

**Oil Sponge IS** requires no extra precautions for storage and handling. It is safe to store in a normal setting and is user-friendly. It is bio-compatible with most bacteria packages and will not harm existing treatment systems.

**Oil Sponge IS** is an amazing product that will not only reduce your carbon footprint but also meets all the standards that are considered to be an environmentally conscious cleaner.



Size	Part #	Pack
5 gallon	61005	48/plt
55 gallon	61055	4/plt

## OIL SPONGE IS CLEANER IS:

Cutting-edge emulsion for heavy-duty degreasing and parts washers where an emulsion-based fluid is desired or required.

### Benefits:

- ▶ Emulsion-Based Degreaser for the toughest industrial needs
- ▶ Bio-Degradable
- ▶ Bio-Compatible
- ▶ Non-Toxic
- ▶ Low Odor suitable for high temperature applications
- ▶ Non-Corrosive
- ▶ No Petro-Chemicals
- ▶ Great Aquatic Toxicity meets standards for "Green Cleaners"

### Oil Sponge IS Cleaner cleans/removes the following:

- ▶ Carbon Build-up
- ▶ Greases/Oils (Petro & Synthetic)
- ▶ Greases/Oils (Animal & Vegetable)
- ▶ Road Grime
- ▶ Smoke & Soot
- ▶ Soils & Dirt (General)

### Oil Sponge IS Cleaner applications:

- ▶ Automobile & Truck Interiors, Exteriors, Engine Compartments
- ▶ Industrial Equipment and Machinery
- ▶ Floors (all water-tolerant flooring)
- ▶ Wood Surfaces (water-tolerant)

### Dilutions:

**Dilute:** 1:1, up to 1:100, depending upon needs, which will be determined by user on-site.

**Heavy-Duty:** 1: to 1:10

**Medium-Duty:** 1:10 to 1:40

**Light-Duty:** 1:40 to 1:100

### Oil Sponge IS Cleaner can be used in:

- ▶ Parts Washers
- ▶ Soak Tanks
- ▶ Pressure Washers
- ▶ Hard-Surface Floor Cleaning Machines
- ▶ Spray or Wipe Processes

### Physical Characteristics:

**Appearance:** Purple Colored Liquid

**Odor:** Negligible

**pH:** 9-10

**Specific Gravity:** 1.01

**Flashpoint:** None

**Solubility:** Infinite

**Storage:** 32° to 120°F

**Volatility:** > 94% (conc.)

**H.M.I.S.:** 1-0-0

**N.F.P.A.:** 1-0-0

Typical dilution for parts washers is 1:6, putting the VOCs at < 30 gms/L, meeting most Air Quality Board requirements. For more stringent areas requiring VOC content to be under 25 gms/L, a 1:6.5 dilution will meet this without any real loss of solvency similar to K-<sup>+</sup>, but adjusted for parts washer usage as well. VOC (Conc.) is 178gms/L.

**Directions for use:** Dilute solution to proper ratio; apply by spray or wipe method. Some mechanical motion may be required to assist in the agitation of the soils. Rinse clean; repeat if necessary.

MANUFACTURED BY:

**PHASE III**



Chandler, AZ 85225  
480.503.2847 p  
480.503.1077 f  
www.phaseiii.com  
www.oilsponge.com

Cleaning Requirement	Light	Medium	Heavy
Label Color	UC	UC+	HD IS
Type of Cleaner	Water-Based		Emulsifier

DISTRIBUTED BY: